



## **Specifications**

| Model                         | H1315NC                                 |
|-------------------------------|---|
| Motor                         | 5 Hp (3.75 kw), 230/460v 3ph*           |
| Hydraulic Pump Motor          | 1 Hp (.75 kw)                           |
| Hydraulic Oil Capacity        | 6.6 gallons (25 liters)                 |
| Blade Speeds (Variable speed) | 66-330 fpm (20-100 m/min)               |
| Blade Size (W x T x L)        | 1.3" x .042 "x 184" (34 x 1.1 x 4240mm) |
| Blade Tension                 | Hydraulic                               |
| Coolant                       | Recirculating                           |
| Coolant Capacity              | 11.9 gallons (45 liters)                |
| 90° Cutting Capacity          |   |
| Round                         | 12.6" (320mm)                           |
| Square                        | 12.6" (320mm)                           |
| Rectangular                   | 15" x 12.6" (380 x 320mm)               |
| **Bundle Cutting Width        | 7.48" to 11.81" (190 to 300mm)          |
| **Bundle Cutting Height       | 2.75" to 5.51" (70 to 140mm)            |
| Feed Length/Index             | 15.86" (403mm)                          |
| Max. Feed                     | 255.9" (6500mm)                         |
| Length                        | 79.13" (2010mm)                         |
| Width                         | 78.75" (2000mm)                         |
| Height                        | 70.3" (1785mm)                          |
| Bed Height                    | 31.1" (790mm)                           |
| Net Weight                    | 4,409 lbs (2000 kg)                     |
| Shipping Weight               | 4,850 lbs (2200 kg)                     |

<sup>\*</sup>Other voltages optional.

Design and specifications are subject to change without notice.

## Toll Free: 800-575-2843 Fax: 888-839-6434

## Clausing/Kalamazoo 12.6" (320mm) Automatic NC Twin Column Bandsaw **Features:**

- Oversized hydraulic cylinder
- Twin column design ensures rigid support during cutting cycle
- Hydraulic shuttle vice assembly
- Inverter controlled infinitely variable speed
- Carbide blade guides with roller bearings
- Two additional guides to support the blade from the top
- Automatic hydraulic blade tensioning
- Power driven blade brushes
- Integral coolant system
- Smart NC-100 technology programmable up to 100 different jobs
- Easy recal and execution of stored parts
- Automatic shutoff after preset number of cuts or when out of stock
- 5.7" HMI touch screen incorporating readout on blade speed, blade life, feed vise position and error code display for self-diagnostics
- Automatic kerf loss compensation & computer controlled multiple indexing
- Precision feed pressure & feed rate
- Bundle/single cutting mode switch
- Automatic height setting feature
- Hydraulic front and rear vises
- Cast iron vises with replaceable hardened wear plates
- Discharge table with built-in coolant return
- Blade slippage or breakage detection
- Adjustable cut-off stock fence
- Additional flushing hose
- Bi-metal saw blade
- Built in work light
- Tool box, leveling pads, and an additional wire brush
- Operation & parts manual
- Two (2) year limited warranty

## Accessories

- Chip Conveyor
- Hydraulic Bundle Clamps
- Variable Vise Pressure System
- Heavy-duty Roller Table 10' x 15"
- Heavy-duty Roller Table 5' x 15"
- Stock Stand Assembly 21" 30"
- SAWZIT 1 Gallon
- SAWZIT 5 Gallon

<sup>\*\*</sup>When machine is equipped with optional hydraulic bundle cutting attachment.