

Cutting Semi-Automatic Miter Bandsaw

Features:


- 0°-45° Miter cutting, make angle cuts without swinging material to be cut
- 2 Hp (1.5kw) main drive with magnetic starter and overload protection
- Variable speed drive
- 230/460v 60 cycle 3 phase electricals
- Recirculating coolant system with application through both guides
- Solid carbide blade guides with rollers
- Quick position vise
- Automatic shut-off at end of cut
- Totally enclosed transmission
- Blade cleaning brush
- Cast iron bed
- 1" (254mm) wide blade
- Stock stop
- Easily adjusted head feed with power lift
- Two (2) year limited warranty

Accessories

- Stock Stand Assembly 21" 30"
- Roller Table Assembly 10' x 18"
- Roller Table Assembly 5' x 18"
- Bandsaw Blade Tension Gauge
- SAWZIT 1 Gallon
- SAWZIT 5 Gallon


Cutting Capacities:

Capacity at 90°



Stock Width in (mm)

Capacity at 45°



Specifications

Model

MS1218VS

| Drive Motor | 2 Hp (1.5kw) 230/460v 3 phase |
|----------------------|-------------------------------|
| Hydraulic Motor | 0.25 Hp (.19kw) |
| Coolant Pump | 0.125 Hp (.1kw) |
| Band Wheel Dia. | 15.4" (391mm) |
| Blade Size | 1" x .035" x 11'-4.5" |
| | (25 x .9 x 3467mm) |
| Bed Height | 21.75" (552mm) |
| Vise Opening | 18" (457mm) |
| Blade Speeds | 80-360 fpm (24-110 m/min) |
| | variable speed |
| 90° Cutting Capacity | |
| Pound | 10" (205mm) |

Round
Square
Rectangular
45° Cutting Capacity

45° Cutting Capacity Round

Square
Rectangular
Width
Depth/with stock stop
Height (head-up)
Height (head-down)

Net Weight

Shipping Weight

12" (305mm)

10" x 10" (254 x 254mm) 10" x 16" (254 x 406mm)

8" (203mm)

8" x 8" (203 x 203mm) 8" x 12" (203 x 305mm)

75" (1905mm)

34"/49.5" (864/1257)mm)

64" (1626mm)

41" (1041mm)

880 lbs (400kg)

1,100 lbs (500kg)