



Specifications

| Model | MS1319NC |
|-------------------------------|---|
| Motor | 5 Hp (3.75 kw), 230/460v 3ph* |
| Hydraulic Pump Motor | 1 Hp (.75 kw) |
| Hydraulic Oil Capacity | 10.4 gallons (40 liters) |
| Blade Speeds (Variable speed) | 66-330 fpm (20-100 m/min) |
| Blade Size (W x T x L) | 1.3" x .042" x 184" (34 x 1.1 x 4670mm) |
| Blade Tension | Hydraulic |
| Coolant | Recirculating |
| Coolant Capacity | 14.3 gallons (55 liters) |
| 90° Cutting Capacity | |
| Round | 13" (330mm) |
| Rectangular | 11" x 19.68" (280 x 500mm) |
| 43° Cutting Capacity | |
| Round | 11.5" (290mm) |
| Rectangular | 10.43" x 10.43" (265 x 265mm) |
| Feed Length/Index | 23.9" (607mm) |
| Max. Feed | 255.9" (6500mm) |
| Length | 114" (2900mm) |
| Width | 102" (2600mm) |
| Height | 86.6" (2200mm) |
| Bed Height | 28.3" (720mm) |
| Net Weight | 3,300 lbs (1500 kg) |
| Shipping Weight | 3,745 lbs (1700 kg) |

^{*}Other voltages optional.

Toll Free: 800-575-2843 Fax: 888-839-6434 Clausing/Kalamazoo 13" (330mm) Automatic **NC Swivel Head Miter** Bandsaw **Features:**

- The swivel sawhead allows cutting at any angle between 90° (straight cut) and 45° (miter cut)
- Precision pivot system facilitates easy and accurate adjustment for angle cuts
- Inverter controlled infinitely variable speed
- Carbide blade guides with roller bearings
- Two additional guides to support the blade from the top
- Automatic hydraulic blade tensioning
- Power driven blade brushes
- Integral coolant system
- Smart NC-100 technology programmable up to 100 different jobs
- Easy recal and execution of stored parts
- Automatic shutoff after preset number of cuts or when out of stock
- 5.7" HMI touch screen incorporating readout on blade speed, blade life, feed vise position and error code display for self-diagnostics
- Automatic kerf loss compensation & computer controlled multiple indexing
- Precision feed pressure & feed rate
- Automatic height setting feature
- Hydraulic front and rear vises
- Cast iron vises with replaceable hardened wear plates
- Computer controlled multiple indexing
- Discharge table with built-in coolant return
- Blade slippage or breakage detection
- Additional flushing hose
- Bi-metal saw blade
- Built in work light
- Tool box, leveling pads, and an additional wire brush
- Operation & parts manual
- Two (2) year limited warranty

Accessories

- Chip Conveyor
- Variable Vise Pressure System
- Heavy-duty Roller Table 10' x 15"
- Heavy-duty Roller Table 5' x 15"
- Stock Stand Assembly 21" 30"
- SAWZIT 1 Gallon
 SAWZIT 5 Gallon

Design and specifications are subject to change without notice.