



Specifications

Model
Drive Motor
Hydraulic Motor
Hydraulic Oil Capacity
Coolant Motor
Coolant Capacity
Blade Speeds (Inf. Variable)
Blade Size
Swivel Angle Range
Cutting Capacity
Round @ 90°

Square @ 90°
Square @ 45°
Square @ 60°
Rectangular @ 90°
Rectangular @ 45°
Rectangular @ 60°
Bed Height
Dimensions:
Length

Round @ 45°

Round @ 60°

Width

Height

Net Weight

Shipping Weight

MS1318SA

3 Hp (2.2kw)
.25 Hp (.19kw)
2 gallons (7.5 liters)
.125 Hp (.1kw)
7.8 gallons (7.5 liters)
102-377 fpm (31-115 m/min)
1" x .035" x 13'-11"
(25 x .9 x 4150mm)
0° to 60°

13" (330mm) 11.5" (292mm) 8.7" (220mm) 10.6" (270mm) 10.5" (268mm) 8.7" (221mm)

18.5" x 10.6" (470 x 269mm) 10.5" x 10.5" (268 x 268mm) 8.7" x 8.7" (220 x 220mm) 33" (838mm)

75" (1905mm) 34" (863mm) 55.5" (1410mm) 1,400 lbs (635kg) 1,850 lbs (839kg)

Toll Free: 800-575-2843 Fax: 888-839-6434

Clausing 13" (330mm) Semi-Automatic Swivel **Head Miter Bandsaw Features:**


- Advanced hydraulic system provides dependable power for powered clamping and raising the saw head at end of cut
- Full stroke machine vise for tight clamping of any material from operator's panel
- Operator's panel pivots allowing operator to control saw from the rear of machine
- Swivel sawhead allows the operator to accurately pivot head for angle cuts from 0°, for a 90° cut, to 60°
- Carbide blade guides provide excellent stability for the saw blade
- Variable blade speed
- Power chip brush removes chips from the blade extending blade life
- Integrated coolant system
- Cast iron moveable guide arms provide rigidity and stability for an accurate cut
- Flushing hose
- Adjustable work stop
- Tool box with tools
- Manual & parts list
- Two (2) year limited warranty

Available in Manual and Automatic Models Accessories

- Stock Stand Assembly 21" 30"
- Roller Table Assembly 10' x 18"
- Roller Table Assembly 5' x 18"
- Bandsaw Blade Tension Gauge
- SAWZIT 1 Gallon
- SAWZIT 5 Gallon

Cutting Capacities:

Capacity at 90°



Capacity at 45°

